

NEO XL-Series Family

Automated Mid Range and Enterprise Data Storage

Helping IT managers keep pace with today's incredible data growth rates



The NEO XL-Series ensures that data is protected faster, smarter, easier and more cost-effectively.

Highlights

- Capacity ranging from 200TB to 16.8PB
- Data transfer rates ranging from 576 Gb/hr. to 113TB/hr.
- Rack-friendly form factor for optimal density & use of valuable rack space
- Intelligent monitoring management and diagnostics
- Ability to scale capacity and performance as needed
- Redundant data path and control path for increased data availability
- Redundant power for enhanced data availability
- Supports encryption key management functionality with a broad range of key management servers
- Includes NEO Agility LTF5 support for disk-like file drag and drop and archive management

Features



Flexible – *Grow into, not out of, your storage*

The scalable design of the NEO XL-Series allows customers to customize their backup and archive solution by starting out with either a 3U, 32-slot or 6U, 80-slot single-drive library and scaling to as many as 560 slots and 42 tape drives. The seamless design of NEOxl libraries allows you to add both data cartridges and tape drives as you scale, instead of requiring you to choose between capacity or performance.

The scalable design of NEOxl libraries not only allows users to easily scale the library into a larger configuration, but it also enables simplified redeployment of individual modules into smaller applications. This flexibility makes NEO XL-Series the most ideal, most cost-effective solution for any midrange or enterprise environment.

For enterprise customers that need maximum performance and capacity right out of the box, NEOxl is available in a fully-configured 560-slot, 42-drive capable library delivered in a standard datacenter rack. NEOxl 8000 includes redundant features optimized for enterprise environments.



Convenient – *Minimize administrative overhead*

NEO XL-Series libraries provide convenient, simplified installation, setup and operation with a touch-screen operator control panel or web-based remote management. Removable cartridge magazines facilitate the loading, unloading and offline storage of data cartridges, reducing media handling costs. Meanwhile, mail slots provide easy, secure access to individual tape cartridges without interrupting library operations, while NEOxl tape drives are easily added, removed or replaced to ensure effortless upgradeability and serviceability.



Cost-Effective – *Get the best return on your investment*

NEO XL-Series libraries are designed to not only provide an affordable purchase price, but to deliver superior long-term cost of ownership. NEO XL-Series ease-of-use features and enterprise-class reliability ensure administrative, support and downtime costs are virtually eliminated, while the native partitioning functionality provides the ability to utilize a single library in a variety of applications.



Dependable – *Backup and archive you can count on*

NEO XL-Series libraries provide the reliability required by today's demanding IT environments to ensure that your data is readily accessible and always available. Features such as redundant power provide access to your data in the event of a power disruption, while easily replaceable tape drives and tape library modules ensure seamless reconfiguration should a support event occur and require replacement.

All NEO XL-Series libraries are covered by a standard one-year, next business day onsite warranty. For customers requiring a higher level of onsite support, customers may upgrade to enhanced next-business day support or 24x7x4 hr. response times for the most mission critical operations.

Specifications

| | Form Factor | # of slots | # of drives | LTO-8 | | LTO-8M | | LTO-7 | | LTO-6 | |
|-----------------------|-------------|------------|-------------|-----------|--------------|-----------|--------------|-----------|--------------|-----------|--------------|
| | | | | Capacity* | Performance* | Capacity* | Performance* | Capacity* | Performance* | Capacity* | Performance* |
| NEOxi 40 | | | | PB | TB/hr. | PB | TB/hr. | PB | TB/hr. | TB | TB/hr. |
| 1 base | 3u | 32 | 3 | 1.0 | 8.1 | 0.7 | 8.1 | 0.5 | 8.1 | N/A | N/A |
| 1 base + 1 expansion | 6u | 72 | 6 | 2.2 | 16.2 | 1.6 | 16.2 | 1.1 | 16.2 | N/A | N/A |
| 1 base + 2 expansions | 9u | 112 | 9 | 3.4 | 24.3 | 2.5 | 24.3 | 1.7 | 24.3 | N/A | N/A |
| 1 base + 3 expansions | 12u | 152 | 12 | 4.6 | 32.4 | 3.4 | 32.4 | 2.3 | 32.4 | N/A | N/A |
| 1 base + 4 expansions | 15u | 192 | 15 | 5.8 | 40.5 | 4.3 | 40.5 | 2.9 | 40.5 | N/A | N/A |
| 1 base + 5 expansions | 18u | 232 | 18 | 7.0 | 48.6 | 5.2 | 48.6 | 3.5 | 48.6 | N/A | N/A |
| 1 base + 6 expansions | 21u | 272 | 21 | 8.2 | 56.7 | 6.1 | 56.7 | 4.1 | 56.7 | N/A | N/A |
| NEOxi 80 | | | | | | | | | | | |
| 1 base | 6u | 80 | 6 | 2.4 | 16.2 | 1.8 | 16.2 | 1.2 | 16.2 | 15.0 | 8.6 |
| 1 base + 1 expansion | 12u | 160 | 12 | 4.8 | 32.4 | 3.6 | 32.4 | 2.4 | 32.4 | 30.0 | 17.3 |
| 1 base + 2 expansions | 18u | 240 | 18 | 7.2 | 48.6 | 5.4 | 48.6 | 3.6 | 48.6 | 45.0 | 25.9 |
| 1 base + 3 expansions | 24u | 320 | 24 | 9.6 | 64.8 | 7.2 | 64.8 | 4.8 | 64.8 | 60.0 | 34.6 |
| 1 base + 4 expansions | 30u | 400 | 30 | 12.0 | 81.0 | 9.0 | 81.0 | 6.0 | 81.0 | 75.0 | 43.2 |
| 1 base + 5 expansions | 36u | 480 | 36 | 14.4 | 97.2 | 10.8 | 97.2 | 7.2 | 97.2 | 90.0 | 51.8 |
| 1 base + 6 expansions | 42u | 560 | 42 | 16.8 | 113.4 | 12.6 | 113.4 | 8.4 | 113.4 | 105.0 | 60.5 |
| NEOxi 8000 | | | | | | | | | | | |
| 1 base | 42u | 560 | 42 | 16.8 | 113.4 | 12.6 | 113.4 | 8.4 | 113.4 | N/A | N/A |

| | NEOxi 40 | NEOxi 80 | NEOxi 8000 |
|--|--|--|--|
| # of mail slots (per module) | 5 | 10 | 70 |
| Tape drive technologies supported | LTO-8, LTO-8M, LTO-7 | LTO-8, LTO-8M, LTO-7, LTO-6 | LTO-8, LTO-8M, LTO-7 |
| Interfaces | 6Gb Mini-SAS, 8Gb LC Optical FC (control path), 1GbE RJ-45 (management) | 6Gb Mini-SAS, 8Gb LC Optical FC (control path), 1GbE RJ-45 (management) | 8Gb LC Optical FC (control path), 1GbE RJ-45 (management) |
| High availability features | Redundant data and control path** | Redundant data and control path**, redundant power | Redundant data and control path**, redundant power |
| # of partitions supported (per module) | Up to 3 | Up to 7 | Up to 24 |
| Library MCBF: | 2,000,000 | >3,000,000 | >3,000,000 |
| Library MTTR: | <10 minutes | <10 minutes | <20 minutes |
| Dimensions (out-of-box; HxWxD) | 5.24 x 18.98 x 34.27 in. (13.3 x 48.2 x 87.3 cm) | 10.55 x 18.7 x 35.1 in. (26.8 x 47.5 x 89.2 cm) | 82.38 x 23.54 x 48.22 in. (209 x 59.8 x 122.5 cm) |
| (shipping; HxWxD) | 12.6 x 27.09 x 45.59 in. (32 x 68.8 x 115.8 cm) | 24.2 x 31.5 x 47.2 in. (61.5 x 80.0 x 120 cm) | 87.8 x 25.2 x 49.6 in. (223 x 64 x 126 cm) |
| Weight (out of box) | 55.34 lbs. (25.1 kg) | 90.4 lbs. (43.6 kg) | 771 lbs. (350 kg) |
| (shipping) | 68.34 lbs. (31 kg) | 120.1 lbs. (54.5 kg) | 1250 lbs. (567 kg) |
| Operating temperature | 50° to 95° F (10° to 35° C) | 50° to 95° F (10° to 35° C) | 50° to 95° F (10° to 35° C) |
| Operating humidity | 20% to 80% | 20% to 80% | 20% to 80% |
| Voltage/Frequency | 100-120V VAC, 3.7A Max., 50/60 Hz | 100-120V, 200-240 VAC, 3.5A Max., 50/60 Hz | 100-120V, 200-240 VAC, 3.5 to 1.5 Amperes, 50/60 Hz |
| Power | 230 Watts (max.) | 200 Watts (max.) | 1400 Watts (max.) |

* assumes 2.5:1 compression

** available in FC configurations

Sales and support for Overland-Tandberg products and solutions are available in over 90 countries.
Contact us today at sales@overlandstorage.com or sales@tandbergdata.com

DS_v5_feb13_2018

©2018 Sphere 3D. All trademarks and registered trademarks are the property of their respective owners. The information contained herein is subject to change without notice and is provided "as is" without warranty of any kind. Sphere 3D shall not be liable for technical or editorial errors or omissions contained herein.